

Technical Information

TECTOFIN[®] Liquid



TECTOFIN liquid is a solvent plasticized membrane material, based on the patented TECTOFIN-composition from high polymeric plastics with ASA (acryl synthetic rubber).

TECTOFIN liquid is used for the seam sealing on the joints and edges of TECTOFIN RG membranes. The main purpose of use is for the capillary sealing for the inner fibre mesh, if this is visible on the membrane edges.

Packaging size: 0,85 kg
Max. storage period: 24 months

Consumption: ca. 20 g/m
Drying time: ca. 1,5 hrs. at 20°C/50%

Marked: UN1993, flammable liquid, n.o.s. class 3
Contains Tetrahydrofuran und Cyclohexanone
For more information, please take a look at our safety data sheets
(<http://www.wolfin.de/sicherheitsdatenblaetter.html#TECTOFIN>)



Further System Accessories:

- | | |
|---|---|
| <ul style="list-style-type: none">• Homogene membrane material for detailing (TECTOFIN[®] R)• Outer corner• Composite metal sheets | <ul style="list-style-type: none">• Stainless steel drainage and ventilation elements• Lightning protection• Installation adhesives for joints: Terokal 914 and Terotech Spray-Adhesive |
|---|---|

Technical Support: +49 6053 708-141

This technical data sheet was created according to the actual technical information and knowledge from WOLFIN Bautechnik GmbH, Am Rosengarten 5, D-63607 Wächtersbach-Neudorf, Germany. Technical changes due to further product developments are possible.